



## H46 C1000

24/120/240 Vac Wall mounted Dehumidistat

- Positive ON-OFF settings permit manual operation of controlled equipment.
- Impact-resistant, molded plastic cover mounts on wall.
- Fully enclosed, dust free, SPST, snap-acting switch.
- sensing element of thin, moisture sensitive nylon ribbon provides reliable operation even when ambient temperature conditions change.

Motor Ratings VAC	120	208	240
AC full load amp	6.0	3.5	3.0
AC locked rotor amp	36.0	21.0	18.0
Pilot Duty - 125 VA, 24 to 277 VAC			

## Product Specifications

Description Wall mounted Dehumidistat

Application Dehumidification

Voltage 120 Vac

Voltage 240 Vac

Voltage 24 Vac

Electrical Ratings (120 Vac, Full Load) 7.5 A

Electrical Ratings (120 Vac, Locked Rotor) 30.0 A

Electrical Ratings (120 Vac, Resistive) 12.0 A

Electrical Ratings (240 Vac, Full Load) 3.8 A

Electrical Ratings (240 Vac, Locked Rotor) 15.0 A

Electrical Ratings (240 Vac, Resistive) 6.0 A

Mounting Wall mount

Differential 4% to 6% RH

Temperature Range (C) 10 C to 52 C

Operating Humidity Range 20 % RH to 80% RH

Dimensions (mm) 119 mm high x 75 mm wide x 54 mm deep