

## RC-3750

### Special Features:

- Fully Automated Control
- High Moisture Capacity
- Low Power Consumption
- Robust design
- Auto-defrost
- Wide range of applications
- Inside Cooler for high efficiency



**RC-3750 is a large capacity, floor standing industrial dehumidifier designed for wide applications. As it provides good air circulation, no ductwork is required during installation. It is ideal for controlling medium range humidity.**

**RC-3750 is built-in with a simple user interface for the ease of operation. The dehumidifier has a built-in humidistat, enabling full automated control at the desired condition. Each unit is built with tight-sealed casing to ensure reliable operation.**

**The RC-3750 is equipped with a dust filter, which can be easily removed for cleaning. The condensate water is allowed to flow out from the drainage pipe, which can be easily extended to the nearby drainage system.**

### Options:

1. Digital humidity control/ monitoring
2. BAS/ DDC interface
3. Water pump to remove condensate water

Technical Data	RC-3750
Condensate Capacity at 25 Deg C 60% RH	130 L/day
Working Range – Humidity	40% - 90%
Working Range – Temperature	20-40 deg C
Air Circulation	2800-3000CMH
Power Supply	400V/ 3phase/ 50Hz
Power Consumption	4.80kW
Dimension (mm): Height X Width X Depth	1465H x 995W x 520D
Drainage pipe	½” treaded
Type of Refrigerant	R-22 (R-417 option available)