

Electro mechanical thermostats

Room thermostat 1-stage



For wall mounting. 1-stage. Mechanical operation by gas-filled stainless steel bellows. For cooling or heating application.

- Bellow type
- 10 A

Technical Data	
Output	10 A (2.5 A) 250 V AC, changeover
Setpoint	5...30°C
Hysteresis	0.6 K
Mounting	Wall-mounting
Protection class	IP30

Description	Type	Leaflet
Room thermostat	TI-N	4-001

Room thermostat



Room thermostat for wall mounting. One or two stages.

- High protection class

Technical Data	
Output	15 A 250 V AC, changeover
Protection class	IP 30 or IP 65

Description	Temperature range	Hysteresis	Step difference	Type	Leaflet
1-stage, IP30	-35...+40°C	2...8°C		A19BBC-9275	
1-stage, IP65	-35...+40°C	2...8°C		A19BRC-9253	
2-stage, IP65	0...+43°C	1.5°C	1...4°C	A28QA-9113	

Duct thermostat



Thermostat with bulb for duct or immersion wall mounting.

Technical Data	
Output	15 A 250 V AC, changeover

Description	Temperature range	Hysteresis	Type	Leaflet
1-stage, IP30	-35...+40°C	2...8°C	A19ABC-9037	

Accessories	Type	Leaflet
Fixture for mounting thermostat bulb in duct	KANALFÄSTE	